

Water based velvety-pearlescent paint.

USAGE

Interior and exterior masonry

PREPARATION

(Ensure surfaces are sound, clean, dry and free from grease.

For all absorbant surfaces (plaster, wood, etc...) apply 1 coat of "Fond de Teint" premium primer.

For any other surface (tiles, plastic etc...) apply "Restart" multi surface primer.

TECHNIQUE

Please consult our HOW-TO sheet for the right technique to apply our Sparkl paint

DILUTION, DRYING AND COVERAGE



Ready to use



Ready to use



Touch dry:
30mn

Recoat:
4 hrs



8 à 12 m²
per liter



Clean Up :
Use warm water
and soap to clean
tools.

PROTECTION

Due to Sparkl's high quality formulation no further protection is needed on walls once Sparkl has dried and hardened. For woodwork you may use our Acrylic Varnish for further protection

COLOURS & PACK SIZE

30 colours + bespoke colours

100ml (18 colours only) / 1 L / 2,5 L

FORMULATION AND TECHNICAL DETAILS

Density : 1,20 g/ltr

Formulation : Modified Acrylic resins, a selection of metallic pigments and binders

Solids by weight : 30 %

Flash Point: In-inflammable

VOC - maximum content: 27gr/ltr

(Fiche technique version 2011/)