



A high quality, water based lacquer which distends to a perfect smoothness. Can be used on any interior or exterior surfaces.

**Kyoto H<sup>2</sup>O exists en Mat, Velvet, Eggshell or High Gloss**

**USAGE**

Interior and exterior masonry and woodwork






**PREPARATION**

(Ensure surfaces are sound, clean, dry and free from grease.  
For all absorbant surfaces (plaster, wood, etc...) apply 1 coat of "Fond de Teint" premium primer.  
For any other surface (tiles, plastic etc...) apply "Restart" multi surface primer.

**TECHNIQUE**

Apply two coats of Kyoto H<sup>2</sup>O using a medium bristled roller or brush.  
When applying deep shaded colours make sure that you have prepared the substrate using the adequately tinted "Fond de teint"

**DILUTION, DRYING AND COVERAGE**

 <p>up to 10% water</p>	 <p>up to 10% water</p>	 <p>Touch dry : 30mn</p> <p>Recoat: 4 hrs</p>	 <p>8 - 12 m<sup>2</sup> per liter</p>	 <p>Clean Up : Use warm water and soap to clean tools.</p>
--	--	--	---	---

**PROTECTION**

Kyoto H<sup>2</sup>O, once dry, has a very high level of mchanical resistance and does not need to be protected.

**COLOURS & PACK SIZE**

147 colours - Inspirations + 1050 colours - Colour Box + bespoke colours  
750ml / 2,5 L / 4L / 14 L (mat only)

**FORMULATION AND TECHNICAL DETAILS**

Density :1,060 à 1,260 g/ltr  
Modified acrylic resins, titanium dioxide and selected fillers  
Solids by weight : 40%  
Flash point : In-inflammable  
Thickness : 40 µm  
VOC - maximum value : < 75gr/ltr - Low  
(Fiche technique version 2011/01)